

[Home](#) >> [Small/Medium Business](#) >> [Products](#) >> [Surge Protection and Power Conditioning](#) >> [Surge Protection Devices](#) >> [Product Family](#)



APC Performance SurgeArrest 11 Outlet with Phone (Splitter) and Coax Protection, 120V

Part Number: P11VT3



Output

Number of Outlets	11
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	8 feet (2.44 meters)
Input Breaker Capacity	15A



Surge Protection and Filtering

Surge energy rating	3400 Joules
EMI/RFI Noise rejection (100 kHz to 10 MHz)	70 dB
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines), Cable modem / Video protection
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 40

Physical

Net Weight	2.33 lbs. (1.06 kg)
Maximum Height	1.57 inches (40 mm)
Maximum Width	

Environmental

Operating Environment	5 - 113 °F (-15 - 45 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$100000
UL 1449 TVSS Rating	330V

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved